



MITASU OIL CORPORATION

105,1-7,3-chome, Kamishinden, Toyonaka, 560-0085, Osaka, Japan
Tel: +81 (0)6 6835 1626, Fax: +81 (0)6 6835 1627
E-mail: japan@mitasuoil.co.jp

quality.always

MJ-131. MITASU JAPAN SL 10W-40

MITASU JAPAN SL 10W-40 is manufactured on the basis of highly purified mineral oil of premium quality. It provides reliable protection and stable lubrication of engine. It complies with technical requirements made for this class of oils. It has increased alkali number for neutralization of sulphur contained in fuel.

APPLICATION

MITASU JAPAN SL 10W-40 is designed for modern four-stroke high-powered gasoline engine, turbo-charged and non-turbocharged. It is suitable for light car, van, light truck and motorboat's engines. Performance and ecological characteristics of the product cover wide range of JASO (Japanese Automotive Standards Organization) standards and complies with the latest requirements of API.

SPECIFICATIONS / APPROVALS

- API SL
- JASO MA

APPLICATION BENEFITS

MITASU JAPAN SL 10W-40 provides:

- Stable performance properties all year round
- Smooth start of the engine
- Perfect antioxidant properties
- Maximal protection from oxidation and rust



Advanced technologies of MITASU OIL CORPORATION, JAPAN, enable the oils manufactured by the company to exceed requirements of the majority car manufactures including, but not limited, the following: TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE Viscosity Grade	SAE J300	10W-40
Specific Gravity at 15°C	ASTM D-4052	0,871
Flash Point, °C	ASTM D-92	226
TBN (mg KOH/g)	ASTM D-2896	9
Pour Point, °C	ASTM D-97	-30
Colour	ASTM D-1500	<3,5
Viscosity Index	ASTM D-2270	156
Kinematic Viscosity at 40°C (cSt)	ASTM D-445	93,6
Kinematic Viscosity at 100°C (cSt)	ASTM D-445	14,2

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2010 Mitsub Oil Corporation. Trademark registered in Japan.



1L



4L



20L



200L