



MITASU OIL CORPORATION

105,1-7,3-chome, Kamishinden, Toyonaka, 560-0085, Osaka, Japan
Tel: +81 (0)6 6835 1626, Fax: +81 (0)6 6835 1627
E-mail: japan@mitasuoil.co.jp

quality.always

MJ-132. MITASU JAPAN SL 20W-50

MITASU JAPAN SL 20W-50 is manufactured on the basis of highly purified base oils of high viscosity, and is the effective development of MITASU OIL CORPORATION, JAPAN. This product provides maximum protection for either new or long-standing gasoline engine.

APPLICATION

MITASU JAPAN SL 20W-50 is designed for intensive conditions of vehicle operation under high ambient temperature. Due to high kinematic viscosity, the product fills up gaps between the cylinder itself and the piston. Performance and ecological characteristics of the product cover wide range of JASO (Japanese Automotive Standards Organization) standards and complies with the latest requirements of API.

SPECIFICATIONS / APPROVALS

- API SL
- JASO MA

APPLICATION BENEFITS

MITASU JAPAN SL 20W-50 provides:

- Stable performance properties under high ambient temperature
- Decrease of oil consumption in worn engines
- Smooth start of the engine
- Perfect antioxidant properties
- Maximum protection from oxidation and rust



Advanced technologies of MITASU OIL CORPORATION, JAPAN, enable the oils manufactured by the company to exceed requirements of the majority car manufactures including, but not limited, the following: TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE Viscosity Grade	SAE SAE J300	20W-50
Specific Gravity at 15°C	ASTM ASTM D-4052	0.893
Flash Point, °C	ASTM ASTM D-92	233
TBN (mg KOH/g)	ASTM ASTM D-2896	7.8
Pour Point, °C	ASTM ASTM D-97	-19
Colour	ASTM ASTM D-1500	3.0
Viscosity Index	ASTM ASTM D-2270	126
Kinematic Viscosity at 40°C (cSt)	ASTM ASTM D-445	195
Kinematic Viscosity at 100°C (cSt)	ASTM D-445	21

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2010 Mitsu Oil Corporation. Trademark registered in Japan.

1L

4L

20L

200L

