



quality.always

MITASU OIL CORPORATION

105,1-7,3-chome, Kamishinden, Toyonaka, 560-0085, Osaka, Japan
Tel: +81 (0)6 6835 1626, Fax: +81 (0)6 6835 1627
E-mail: japan@mitasuoil.co.jp

MJ-431. MITASU JAPAN GL-5 80W-90



1L



4L



20L

MITASU JAPAN GL-5 80W-90 is universal gear oil manufactured on the bases of special highly purified oil with reliable sulphur and phosphoric additives. It is developed for better performance at extreme loads. It contains antifoaming additives to reduce foam formation. Excellent sulphur and phosphoric additives maintain good condition of sealing and gaskets. MITASU JAPAN GL-5 80W-90 guarantees excellent friction protection of heavy-load engine parts.

APPLICATION

MITASU JAPAN GL-5 80W-90 is suitable for heavy-load worm and hypoid gearings, vehicle transmissions, transfer gear-boxes, balancers, rear axles and steering mechanisms of passenger and cargo vehicles, building and farm machinery where high-performance oil is recommended. Moreover, it may be used in gearboxes, where API GL-4 specification is recommended. Technical specifications MITASU JAPAN GL-5 80W-90 allow using it all year round at wide temperature range.

APPLICATION BENEFITS

- All-purpose product, suitable for heavy trucks and lorries, buses and passenger cars
- Strong protection of manual transmissions at high and low speeds due to sulphur and phosphoric additives
- Excellent oxidation and rust protection



Advanced technologies of MITASU OIL CORPORATION, JAPAN, enable the oils manufactured by the company to exceed requirements of the majority car manufactures including, but not limited, the following: TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE Viscosity Grade	SAE J300	80W-90
Specific Gravity at 15°C	ASTM D-4052	0,905
Flash Point, °C	ASTM D-92	214
Pour Point, °C	ASTM D-97	-27
Colour	ASTM D-1500	4
Viscosity Index	ASTM D-2270	100
Kinematic Viscosity at 40°C (cSt)	ASTM D-445	120,60
Kinematic Viscosity at 100°C (cSt)	ASTM D-445	15,25

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2010 Mitsuru Oil Corporation. Trademark registered in Japan.