



quality.always

# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

## MJ-105. MITASU GOLD SN 10W-30 100% Synthetic

MITASU GOLD SN 10W-30 100% Synthetic is a fully synthetic resource conserving motor oil is blended from a fully synthetic base and the patented ZDDP anti-wear additive package to provide maximum protection for modern gasoline fuelled engines. It meets the GM standard dexos1 and GF-5 oil specifications for gasoline engines set by International Lubricants Standardization and Approval Committee (ILSAC).

### APPLICATION

MITASU GOLD SN 10W-30 100% Synthetic has been designed for modern cars and exceeds the most demanding requirements for modern engine emission control and fuel efficiency. It provides protection from oxidation. It has been designed for all-season use.

### SPECIFICATIONS / APPROVALS

- API SN
- ILSAC GF-5
- dexos1



### APPLICATION BENEFIT

All-season MITASU GOLD SN 10W-30 100% Synthetic provides:

- OEM level of quality
- Low oil consumption through burning
- Emission system durability
- Engine cleanliness
- Fuel economy
- Seal protection

The ZDDP anti-wear additive package delivers much less phosphorous on the face of the catalyst, significantly reducing the poisoning of the catalyst system.

The latest technologies of MITASU OIL CORPORATION, Japan and the ILSAC GF-5 standard enable MITASU GOLD SN 10W-30 100% Synthetic to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, INFINITI, HONDA, ACURA, MAZDA, SUZUKI, SUBARU, MITSUBISHI, DAIHATSU, CHRYSLER, CHEVROLET, FORD, HYUNDAI, KIA and others.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-30
Density at 15°C	ASTM D-4052	0,8559
Flash point, °C	ASTM D-92	216
TBN (mg KOH/g)	ASTM D-2896	7,80
Pour point, °C	ASTM D-97	-36
Colour	ASTM D-1500	<3,0
Viscosity index	ASTM D-2270	160
Kinematic viscosity at 40°C (cSt)	ASTM D-445	65,79
Kinematic viscosity at 100°C (cSt)	ASTM D-445	10,96

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2022 Mitsu Oil Corporation, Japan.

1L

4L

5L

6L

20L

200L

