



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-122A. MITASU MOTOR OIL LL SN 10W-40 Synthetic Blended

MITASU MOTOR OIL LL SN 10W-40 Synthetic Blended manufactured from high quality synthetic components and intensified with a group of balanced additives. It conforms to the latest API (American Petroleum Institute) service standard – SN and ensures a high degree of engine protection against wear and prevents sediment formation on engine parts.

APPLICATION

MITASU MOTOR OIL LL SN 10W-40 Synthetic Blended meets the requirements of gasoline-fuelled and light diesel vehicles equipped with direct fuel injection engines with variable valve timing systems and turbocharged or non-turbocharged engines, built to the latest environmental standards. Extended life of catalytic converters protects engines, operating under high loads conditions and in a start-stop mode. Recommended for all-season use.

SPECIFICATIONS / APPROVALS

- API SN/CF
- ACEA A3/B3
- ACEA A3/B4
- MB-Approval 229.3



1L



4L



5L



20L



200L

APPLICATION BENEFITS

Synthetic blended motor oil MITASU MOTOR OIL LL SN 10W-40 Synthetic Blended provides:

- Minimum oil consumption through burning
- Compatibility with all types of catalyts
- Excellent protection against engine wear
- Extended drain interval
- Cleanliness of engine
- Improved compatibility with seal materials

The latest technologies of MITASU OIL CORPORATION, Japan enable oils manufactured by the company to meet and exceed the requirements of most Japanese, American and European Original Equipment Manufacturers (OEM), including: TOYOTA, LEXUS, NISSAN, MAZDA, HONDA, SUZUKI, MITSUBISHI, SUBARU, DAIHATSU, ISUZU, GM, MERCEDES-BENZ, RENAULT, FIAT, SSANGYONG, HYUNDAI, KIA and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-40
Density at 15°C	ASTM D-4052	0,8655
Flash point, °C	ASTM D-92	224
TBN (mg KOH/g)	ASTM D-2896	10,10
Pour point, °C	ASTM D-97	-36
Colour	ASTM D-1500	3,0
Viscosity index	ASTM D-2270	158
Kinematic viscosity at 40°C (cSt)	ASTM D-445	93,31
Kinematic viscosity at 100°C (cSt)	ASTM D-445	14,30

Due to continual product research and development, the information contained herein is subject to change without notification.