



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-122. MITASU MOTOR OIL SM 10W-40 Synthetic Blended



1L



4L



20L



200L

MITASU MOTOR OIL SM 10W-40 Synthetic Blended is an all season oil for gasoline engines, manufactured from Group II and Group III base oils utilizing high quality synthetic components and intensified with a group of balanced additives. It ensures a high degree of engine protection against wear and prevents sediment formation on engine parts.

APPLICATION

MITASU MOTOR OIL SM 10W-40 Synthetic Blended is designed for use in a wide range of temperatures. Meets the requirements of most modern vehicles equipped with direct fuel injection engines with variable valve timing systems and turbocharged or non-turbocharged engines built to the latest environmental standards. It extends the life of catalytic converters. The performance and environmental qualities of this product meet or exceed the requirements of leading American and European centers for API, ACEA and MERCEDES-BENZ.

SPECIFICATIONS / APPROVALS

- API SM
- ACEA A3/B3-04
- ACEA A3/B4-04
- MERCEDES-BENZ 229.1



APPLICATION BENEFITS

MITASU MOTOR OIL SM 10W-40 Synthetic Blended provides:

- Stable performance characteristics all year around
- Improved compatibility with all types of catalysts
- Excellent protection against engine wear
- Protection against rust

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MAZDA, HONDA, MITSUBISHI, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, VW and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-40
Density at 15°C	ASTM D-4052	0,8607
Flash point, °C	ASTM D-92	224
TBN (mg KOH/g)	ASTM D-2896	7,50
Pour point, °C	ASTM D-97	-36
Colour	ASTM D-1500	<3,0
Viscosity index	ASTM D-2270	167
Kinematic viscosity at 40°C (cSt)	ASTM D-445	96,24
Kinematic viscosity at 100°C (cSt)	ASTM D-445	15,21

Due to continual product research and development, the information contained herein is subject to change without notification.