



# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

quality.always

## MJ-124. MITASU MOTOR OIL SL 10W-40 Synthetic Blended



1L



4L



20L



200L

MITASU MOTOR OIL SL 10W-40 Synthetic Blended is semi-synthetic motor oil formulated with highly refined base oils and high performance synthetic components fortified by a powerful high-tech package of detergent/dispersant additives that block the negative effect of aromatic benzene hydrocarbons contained in poor quality gasoline, and reduce deposits in the combustion chamber when using compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG). Provides high protection from oxidation and nitration. Ensures engine protection in all-season environments.

### APPLICATION

MITASU MOTOR OIL SL 10W-40 Synthetic Blended is designed for use in a wide range of temperatures. Meets the requirements of vehicles developed prior to 2005 equipped with direct fuel injection engines with variable valve timing systems and catalytic converters, turbocharged or non-turbocharged engines built to the EURO-3 environmental standards. It can also be used in motorcycle four-stroke engines with an integrated gearbox. It can also be used in engines operating on gaseous fuel, where mid-ash oils with higher valve wear protection are recommended.

### SPECIFICATIONS / APPROVALS

- API SL/CF

### APPLICATIONS BENEFITS

MITASU MOTOR OIL SL 10W-40 Synthetic Blended stands out because of its competitive combination of a wide range of application and low cost. The product provides:

- Stable performance characteristics all year around
- Excellent engine wear protection including gas engines
- Minimum level of sludge and varnish deposits in the engine
- Exceptional resistance to aeration, oxidation and nitration
- Decrease of oil consumption through burning
- Easy engine start

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as CHEVROLET, DAEWOO, TOYOTA, NISSAN, MAZDA, MITSUBISHI, SUZUKI, DAIHATSU, HYUNDAI, KIA and other.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-40
Density at 15°C	ASTM D-4052	0,8631
Flash point, °C	ASTM D-92	222
TBN (mg KOH/g)	ASTM D-2896	7,00
Pour point, °C	ASTM D-97	-36
Colour	ASTM D-1500	<3,0
Viscosity index	ASTM D-2270	162
Kinematic viscosity at 40°C (cSt)	ASTM D-445	98,62
Kinematic viscosity at 100°C (cSt)	ASTM D-445	15,10



Due to continual product research and development, the information contained herein is subject to change without notification.