



quality.always

# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
 E-mail: info@mitasuoil.co.jp

## MJ-126. MITASU MOTOR OIL SL/CF 20W-50 Synthetic Blended



1L



4L



5L



20L



200L

MITASU MOTOR OIL SL/CF 20W-50 Synthetic Blended is a high viscosity engine oil formulated with advanced performance synthetic components and high-tech additives. The product contains a special additive that provides exceptional resistance to oxidation and nitration as well as reduces the build-up of combustion chamber deposits from CNG, LNG and LPG fuel.

### APPLICATION

MITASU MOTOR OIL SL/CF 20W-50 Synthetic Blended is intended for hot climates and is also recommended for high-mileage engines in warmer seasons. It meets the requirements of petrol and diesel turbocharged and non-turbocharged engines including those equipped with direct fuel injection, variable valve timing system and catalytic converter installed on passenger cars, minivans and light trucks. It can be used in engines operating on gaseous CNG, LNG and LPG fuel where mid-ash oils with higher valve wear protection are recommended. The product guarantees engine protection at high ambient temperatures.

### SPECIFICATIONS / APPROVALS

- API SL/CF
- JASO MA



### APPLICATION BENEFITS

Due to its high antioxidant capacity MITASU MOTOR OIL SL/CF 20W-50 Synthetic Blended has a wide range of applications. The product provides:

- Versatility and can be used in petrol, diesel and gas engines
- Stable performance characteristics in high ambient temperatures
- Exceptional resistance to aeration, oxidation and nitration
- Low oil consumption through burning

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, NISSAN, MITSUBISHI, MAZDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, DAEWOO, VW, RENAULT, PEUGEOT and the others.

### TECHNICAL CHARACTERISTICS

Technical Property	Method	Result
SAE viscosity grade	SAE J300	20W-50
Density at 15°C	ASTM D-4052	0,8930
Flash point, °C	ASTM D-92	232
TBN (mg KOH/g)	ASTM D-2896	7,20
Pour point, °C	ASTM D-97	-18
Colour	ASTM D-1500	2,5
Viscosity index	ASTM D-2270	124
Kinematic viscosity at 40°C (cSt)	ASTM D-445	192,20
Kinematic viscosity at 100°C (cSt)	ASTM D-445	20,50

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2019 Mitsuru Oil Corporation, Japan.