



# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

quality.always

## MJ-130. MITASU MOTOR OIL SL 10W-30



1L



4L



200L

MITASU MOTOR OIL SL 10W-30 is motor oil designed for gasoline engines and formulated with highly purified base stocks. It is intensified by a package of high technological detergents and dispersant additives for alleviating the negative effects of benzene series aromatic hydrocarbons contained in unstable gasoline. Provides high protection from oxidation. Designed for all-season use.

### APPLICATION

MITASU MOTOR OIL SL 10W-30 is recommended for use in a wide range of temperatures. Meets the requirements of vehicles developed prior to 2005 equipped with direct fuel injection engines with catalytic converters, turbocharged engines built to the current environmental standards. It can also be used in motorcycle four-stroke engines with integrated gearboxes. The performance and environmental qualities of this product meet the requirements of JASO and API standards.

### SPECIFICATIONS / APPROVALS

- API SL/CF
- JASO MA



### APPLICATION BENEFITS

MITASU MOTOR OIL SL 10W-30 is a premium quality product, which provides:

- Stable performance characteristics all-year-round
- Easy engine start
- Protection against rust

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, HONDA, MAZDA, GM, MITSUBISHI, SUZUKI, SUBARU, DAIHATSU, GM, HYUNDAI, KIA, FORD, MERCEDES-BENZ and 4T motorcycle manufacturers such as: HONDA, SUZUKI, YAMAHA and others.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-30
Density at 15°C	ASTM D-4052	0,8756
Flash point, °C	ASTM D-92	220
TBN (mg KOH/g)	ASTM D-2896	9,50
Pour point, °C	ASTM D-97	- 30
Colour	ASTM D-1500	<4,0
Viscosity index	ASTM D-2270	144
Kinematic viscosity at 40°C (cSt)	ASTM D-445	73,30
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,20

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2014 Mitsuru Oil Corporation, Japan.