



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitsuoi.co.jp

quality.always

MJ-212. MITASU ULTRA DIESEL CI-4 5W-40 100% Synthetic

MITASU ULTRA DIESEL CI-4 5W-40 100% Synthetic is a fully synthetic diesel oil formulated with a unique group of premium quality additives. The high TBN level neutralizes the harmful effects of sulphur contained in low quality diesel fuel.



1L



4L



6L



20L



200L

APPLICATION

MITASU ULTRA DIESEL CI-4 5W-40 100% Synthetic is recommended for all-season use in modern highly accelerated diesel engines of motor cars, vans, SUVs and light trucks with turbocharged or non-turbocharged engines. It ensures easy start maintaining oil fluidity under low ambient temperatures. Top performance and environmental qualities of this product meet the modern requirements of API.

SPECIFICATIONS/APPROVALS

- API CI-4/CH-4/CG-4/CF
- ACEA A3/B3/B4/E3/E5



APPLICATION BENEFITS

Fully synthetic diesel oil MITASU ULTRA DIESEL CI-4 5W-40 100% Synthetic provides:

- A stable oil film protecting engine parts in intensive operating conditions
- Significant extension of drain interval
- Easy engine start at temperatures as low as - 42°C
- High protection from oxidation

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, NISSAN, MITSUBISHI, MAZDA, ISUZU, HYUNDAI, KIA, FORD, GM, VW, FIAT, VOLVO, AUDI, MERCEDES-BENZ, RENAULT and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-40
Density at 15°C	ASTM D-4052	0,8575
Flash point, °C	ASTM D-92	224
TBN (mg KOH/g)	ASTM D-2896	11,20
Pour point, °C	ASTM D-97	- 42
Colour	ASTM D-1500	3,0
Viscosity index	ASTM D-2270	172
Kinematic viscosity at 40°C (cSt)	ASTM D-445	85,70
Kinematic viscosity at 100°C (cSt)	ASTM D-445	14,22

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2012 Mitsasu Oil Corporation, Japan.