



# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

quality.always

## MJ-220. MITASU SUPER DIESEL CI-4 5W-30 Synthetic Blended



1L



4L



6L



20L



200L

MITASU SUPER DIESEL CI-4 5W-30 Synthetic Blended is a synthetic blended diesel oil manufactured from base oils. It is intensified with a group of high technological additives, which improve the energy efficiency, viscosity, temperature and anti-wear properties. The high TBN level neutralises the harmful effects of sulphur contained in low quality diesel fuel.

### APPLICATION

MITASU SUPER DIESEL CI-4 5W-30 Synthetic Blended is recommended for all-season use in modern highly accelerated diesel engines of motorcars, vans, SUVs and light trucks with turbocharged or non-turbocharged engines. It assures reliable engine start in low ambient temperatures and protects from oxidation. The performance and environmental qualities of this product meet the modern requirements of API.

### SPECIFICATIONS / APPROVALS

- API CI-4/CH-4/CG-4/CF
- ACEA A3/B3/B4/E3/E5



### APPLICATION BENEFITS

MITASU SUPER DIESEL CI-4 5W-30 Synthetic Blended provides:

- Easy engine start at temperatures as low as - 40°C
- A stable oil film protecting engine parts
- Extended drain interval
- Protection against rust

The latest technologies of MITASU OIL CORPORATION, Japan enable transmissions oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, NISSAN, MAZDA, MITSUBISHI, ISUZU, HYUNDAI, KIA, FORD, GM, CHRYSLER, RENAULT, FIAT, VOLVO, VW, AUDI, MERCEDES-BENZ и других.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-30
Density at 15°C	ASTM D-4052	0,8542
Flash point, °C	ASTM D-92	220
TBN (mg KOH/g)	ASTM D-2896	10,80
Pour point, °C	ASTM D-97	- 40
Colour	ASTM D-1500	< 3,0
Viscosity index	ASTM D-2270	161
Kinematic viscosity at 40°C (cSt)	ASTM D-445	58,98
Kinematic viscosity at 100°C (cSt)	ASTM D-445	10,29

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2012 Mitsasu Oil Corporation, Japan.