



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
 E-mail: info@mitasuoil.co.jp

quality.always

MJ-309. MITASU ATF 9 HP 100% Synthetic

MITASU ATF 9 HP 100% is an energy-saving fluid made with the PAO base and innovative technology, patented by the Japanese company Mitsui Chemicals, to meet the requirements of modern ZF 9-speed automatic transmissions. It can also be used in ZF 6- and 8-speed transmissions. The product is providing with exceptional fluidity at low temperatures and high viscosity properties throughout its life cycle between changes. The product colour is light-green.



1L



4L



20L



200L

APPLICATION

MITASU ATF 9 HP 100% Synthetic is designed for a wide range of modern European, American and Asian cars, minivans and SUVs equipped with modern ZF 9-, 8- and 6-speed automatic transmissions with the recommended fluids including MOPAR ZF 8 & 9 SPEED ATF, ZF LifeguardFluid 9, HONDA ATF-TYPE 3.1 and their analogues.

SPECIFICATIONS / APPROVALS

- ZF LIFEGUARDFLUID 6 / 8 / 9
- ZF S671 090 312 / AA01.500.001
- BMW ATF 3+
- BMW L12108 (83 22 2 152 426)
- BMW 83 22 2 289 720
- VW Group G 060 162
- VW Group G 055 162
- LAND ROVER LR 023288
- LAND ROVER LR 023289
- JAGUAR 02JDE 26444
- HONDA / ACURA ATF-TYPE 3.1
- HONDA 08200-9017
- HONDA 08263-999-01HE
- HONDA / ACURA ATF-TYPE 3.0
- HONDA / ACURA 08200-9016A
- CHRYSLER 68157995AA
- MOPAR 68218925AA
- MOPAR 68157995AB
- MOPAR ZF 8 & 9 SPEED ATF
- FIAT 9.55550-AV5

APPLICATION BENEFITS

MITASU ATF 9 HP 100% Synthetic provides:

- Innovative alternative to OEM-fluids for modern 9-speed transmissions
- Stable performance in a wide range of temperatures
- Improved anti-vibration properties
- High anti-foaming properties
- Significant fuel efficiency
- Maximum protection of friction surfaces
- Excellent wear and corrosion protection



The latest technologies of MITASU OIL CORPORATION, Japan enable automatic transmission fluids manufactured by the company to exceed the requirements of such car manufacturers as BMW, AUDI, VW, HONDA, ACURA, CHRYSLER, DODGE, JEEP, JAGUAR, LAND ROVER, FIAT and the others.

TECHNICAL CHARACTERISTICS

Technical Properties	Method	Result
Density at 15°C	ASTM D-4052	0,8360
Flash point, °C	ASTM D-92	208
Pour point, °C	ASTM D-97	-42
Colour	Visual	Light Green
Viscosity index	ASTM D-2270	174
Kinematic viscosity at 40°C (cSt)	ASTM D-445	27,20
Kinematic viscosity at 100°C (cSt)	ASTM D-445	5,96

Due to continual product research and development, the information contained herein is subject to change without notification.