



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-312. MITASU CVT FLUID TC Synthetic Tech

MITASU CVT FLUID TC Synthetic Tech is a fluid for continuously variable transmissions, manufactured in accordance with OEM Toyota CVT Fluid TC standard, made based on synthetic technology and a unique additive package. It features anti-foaming properties and excellent vibration-resistance. The product color is red.

APPLICATION

MITASU CVT FLUID TC Synthetic Tech is designed for application in a continuously variable transmissions (CVT), where TOYOTA CVT Fluid TC type is recommended. The product properties are optimized to meet the requirements of TOYOTA fluids for continuously variable transmissions.

THIS PRODUCT MEETS THE REQUIREMENTS OF

- TOYOTA CVT Fluid TC
- TOYOTA 08886-02105
- TOYOTA 08886-02103



APPLICATION BENEFITS

MITASU CVT FLUID TC Synthetic Tech provides:

- Compliance with the requirements of OEM (Original Equipment Manufacturer) TOYOTA
- Exceptional anti-vibration properties
- Correct CVT operation under different operating conditions
- Excellent wear protection

The latest technologies of MITASU OIL CORPORATION, Japan enable continuously variable fluids manufactured by the company to meet the requirements of wide range of modern car manufacturers

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8491
Flash point, °C	ASTM D-92	192
Pour point, °C	ASTM D-97	-45
Colour	Visual	Red
Viscosity index	ASTM D-2270	214
Kinematic viscosity at 40°C (cSt)	ASTM D-445	30,25
Kinematic viscosity at 100°C (cSt)	ASTM D-445	7,15

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2023 Mitsu Oil Corporation, Japan.

1L

4L

20L

200L

