



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
 E-mail: info@mitasuoil.co.jp

quality.always

MJ-322. MITASU CVT FLUID 100% Synthetic



1L



4L



20L



200L

MITASU CVT FLUID 100% Synthetic is a fully synthetic transmission fluid for automobiles with continuously variable transmission (CVT). Excellent technical specifications of this product ensure the proper operation of a variable speed type transmission in various types of operating modes. Product's high viscosity index helps to minimize the negative effects of the intensive operating conditions. It has excellent antivibration properties. The product color is neutral.

APPLICATION

MITASU CVT FLUID 100% Synthetic is used for a wide range of cars with variable-speed gear. It is suitable for some hydraulic transmissions, servo-controlled mechanisms and hydraulic systems.

SPECIFICATIONS / APPROVALS

Fully suitable for the following types of continuously variable transmissions:

- TOYOTA CVT FLUID TC
- NISSAN CVT FLUID NS-2*
- MITSUBISHI DIAQUEEN CVT FLUID J1
- MITSUBISHI CVT ATF SP-III
- MAZDA CVT FLUID 3320
- HYUNDAI/KIA (SP-III)
- SUZUKI SCVT FLUID, CVT OIL
- SUZUKI CVT FLUID GREEN 1
- SUBARU i-CVT FLUID
- SUBARU i-CVT FLUID FG
- DAIHATSU AMIX CVT FLUID DC
- FORD CVT FLUID 23
- GM/SATURN (DEX-CVT)
- MERCEDES-BENZ 236.20



*Note: Not suitable for NISSAN EXTROID CVT FLUID KTF-1

APPLICATION BENEFITS

MITASU CVT FLUID 100% Synthetic provides:

- Stable performance in the wide range of temperatures
- Proper operation of a variable speed type transmissions in various types of operating modes
- Wide range of application

The latest technologies of MITASU OIL CORPORATION, Japan enable fluids for automobiles with continuously variable transmission (CVT) manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MITSUBISHI, MAZDA, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, GM, CHRYSLER, MERCEDES-BENZ and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8490
Flash point, °C	ASTM D-92	190
Pour point, °C	ASTM D-97	-45
Colour	Visual	Neutral Yellow
Viscosity index	ASTM D-2270	200
Kinematic viscosity at 40°C (cSt)	ASTM D-445	29,19
Kinematic viscosity at 100°C (cSt)	ASTM D-445	6,72

Due to continual product research and development, the information contained herein is subject to change without notification.