



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-323. MITASU MULTI VEHICLE ATF Synthetic Blended



1L



4L



20L



200L

MITASU MULTI VEHICLE ATF Synthetic Blended is a high-performance all-purpose automatic transmission fluid, suitable for different applications. The innovative formulation of this product provides smooth gear shifting in automatic transmissions. A high viscosity index ensures efficient lubrication of parts at the highest operational temperatures and lowest start temperatures. MITASU MULTI VEHICLE ATF Synthetic Blended meets the requirements of JASO 1A (Japanese Automotive Standards Organization) tests and HONDA. The product color is red.

APPLICATION

MITASU MULTI VEHICLE ATF Synthetic Blended is widely used in Japanese, European and American cars. This fluid has excellent anti-shudder durability and is suitable for some hydraulic transmissions, servo-controlled mechanisms and hydraulic systems. It can be used as a CVT fluid replacement for units with engine capacity under 2 liters and meets LFW-1 test requirements.

APPROVALS / TECHNOLOGY MEETS REQUIREMENTS

Fully suitable for the following models of automatic and continuously variable transmissions:

- TOYOTA ATF TYPE T-IV, T-III, D-III, D-II
- TOYOTA JWS 2312D, JWS 3309
- TOYOTA #08886-81015, #08886-00405
- NISSAN MATIC FLUID K, J, D
- MITSUBISHI DIAQUEEN ATF SP-III, SP-II
- MITSUBISHI ATF J-2, PSF-3, ATF II
- MAZDA ATF M-V, F-1, M-III
- HONDA ULTRA ATF-1, ATF Z-1
- SUZUKI AT OIL, OIL Special, SCVT
- SUZUKI ATF 5D06, 2384K, 3314, 3317
- SUBARU ATF, ATF HP, ATF (5AT)
- ISUZU BESCO ATF III, II
- DAIHATSU AMIX ATF D-III MULTI/D3-SP
- HYUNDAI/KIA: SP-III, SP-II, Red-1
- HINO Blue Ribbon ATF
- CHRYSLER ATF +3/+4
- FORD M, MERCON
- MERCEDES-BENZ 236.9
- AUDI/VW G-052-025-A1/A2
- PORSCHE JWS 3309



APPLICATION BENEFITS

MITASU MULTI VEHICLE ATF Synthetic Blended provides:

- Stable performance in the wide range of temperatures
- Proper operation of an automatic transmissions in various types of operating modes
- Maximum friction reduction
- Wide range of application

The latest technologies of MITASU OIL CORPORATION, Japan enable fluids for automatic transmissions manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MITSUBISHI, MAZDA, HONDA, SUZUKI, SUBARU, ISUZU, DAIHATSU, HYUNDAI, KIA, FORD, GM, CHRYSLER, VW, AUDI, PORCHE, MERCEDES-BENZ and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8545
Flash point, °C	ASTM D-92	208
Pour point, °C	ASTM D-97	-45
Colour	Visual	Red
Viscosity index	ASTM D-2270	171
Kinematic viscosity at 40°C (cSt)	ASTM D-445	31,71
Kinematic viscosity at 100°C (cSt)	ASTM D-445	6,63

Due to continual product research and development, the information contained herein is subject to change without notification.