



# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
 E-mail: info@mitasuoil.co.jp

quality.always

## MJ-328. MITASU PREMIUM MULTI VEHICLE ATF 100% Synthetic

MITASU PREMIUM MULTI VEHICLE ATF 100% Synthetic is a fully synthetic all-purpose transmission fluid manufactured using advanced new generation additives. Meets a wide range of requirements for the ATF type automatic transmission fluids and guarantees the mileage up to 100,000 km. The product color is neutral.



1L



4L



20L



200L

### APPLICATION

MITASU PREMIUM MULTI VEHICLE ATF 100% Synthetic specifically formulated for automatic transmissions operating under heavy load conditions. Ideal for modern passenger vehicles, buses, trucks and taxis, which require longer transmission lifetime and extended drain interval. It is recommended by Mitsuru Oil for use with following OEM

### SPECIFICATIONS AND APPROVALS

- AUDI/VW G-052-025-A2
- AUDI/VW G-052-162-A1
- AUDI/VW G-052-990 A1/A2
- AUDI/VW G-055-025 A1/A2
- BMW 7045E (3 Series)
- BMW ETL-8072B (5 Series)
- BMW LA2634, LT71141 (ZF 5 Speed)
- CHRYSLER ATFs, MOPAR AS68RC
- DEXRON II, IID, IIE, IIIF, IIIG, IIHH
- FORD MERCON V, FNR5
- HONDA ATF-Z1
- HYUNDAI SP-II, SP-III
- JASO 1A
- JATCO 3100 PL085
- IDEMITSU K17-Jaguar X Type 2001-2005
- KIA SP-II, SP-III
- MAN 339F/V1/V2/Z1/Z2
- MERCEDES-BENZ 236.1/2/3/5/6/7/9/10/11
- MAZDA ATF-M III, ATF-MV
- MITSUBISHI DIAMOND SP-II, SP-III
- NISSAN N402 (JATCO FWD in Nissan)
- NISSAN MATIC D, J, K
- PORSCHE JWS 3309
- SUBARU ATF, ATF-HP
- SUZUKI 3314, 3317, 2384K
- TOYOTA T-III, T-IV
- TEXACO N402 (JATCO FWD in Rover 800 and VW Polo)
- VOITH 55.6335.XX (G607)
- VOLVO 97340, 97341
- ZF TE-ML 03D, 04D
- ZF 11B, 14A, 14B, 16L, 17C

### APPLICATION BENEFITS

MITASU PREMIUM MULTI VEHICLE ATF 100% Synthetic is recommended by Mitsuru Oil for use in applications, where the OEM specifies a fluid, providing performance capability, guaranteeing the mileage up to 100,000 km. and provides:

- Compliance with American, European and Japanese carmakers requirements adds special value for mixed fleet and service stations operators
- Excellent antivibration properties
- Smooth gear shifting throughout fluid life
- Excellent protection against transmission wear
- Wide range of application

The latest technologies of MITASU OIL CORPORATION, Japan enable fluids for automatic transmissions manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MITSUBISHI, MAZDA, HONDA, SUZUKI, SUBARU, ISUZU, DAIHATSU, HYUNDAI, KIA, FORD, GM, CHRYSLER, VW, AUDI, PORCHE, BMW, MB and others.

### TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8528
Flash point, °C	ASTM D-92	236
Pour point, °C	ASTM D-97	-45
Colour	Visual	Neutral
Viscosity index	ASTM D-2270	165
Kinematic viscosity at 40°C (cSt)	ASTM D-445	35,55
Kinematic viscosity at 100°C (cSt)	ASTM D-445	7,05

Due to continual product research and development, the information contained herein is subject to change without notification.