



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-331. MITASU ATF WS Synthetic Tech



1L



4L



20L



200L

MITASU ATF WS Synthetic Tech is a low viscosity automatic transmission fluid made based on synthetic technology. The product has excellent anti-vibration properties and complies with international standards and requirements of TOYOTA, AISIN WARNER and GM for the ATF WS type automatic transmission fluids. The product color is red.

APPLICATION

MITASU ATF WS Synthetic Tech is designed for modern AISIN WARNER automatic transmissions used in TOYOTA, LEXUS and GM vehicles. It can also be used in automatic transmissions of other cars manufacturers where ATF WS fluid is recommended.

THIS PRODUCT MEETS THE REQUIREMENTS OF

- TOYOTA / LEXUS / SCION ATF WS
- TOYOTA / LEXUS / SCION 08886-02303
- TOYOTA / LEXUS / SCION 08886-02305
- TOYOTA / LEXUS / SCION 08886-80803
- TOYOTA / LEXUS / SCION 08886-80807
- TOYOTA / LEXUS / SCION 08886-81210
- AISIN WARNER NWS-9638 / 9638 T5
- AISIN WARNER JWS-3324
- GM 88863400 / 401



APPLICATION BENEFITS

MITASU ATF WS Synthetic Tech provides:

- Fuel efficiency
- OEM (Original Equipment Manufacturer) specified quality
- Stable performance in a wide range of temperatures
- Improved anti-vibration properties
- Proper functioning of automatic transmissions under various operating conditions
- Excellent wear protection

The latest technologies of MITASU OIL CORPORATION, Japan enable automatic transmission fluids manufactured by the company to exceed the requirements of car manufacturers such as TOYOTA, LEXUS, DAIHATSU, GM and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8493
Flash point, °C	ASTM D-92	214
Pour point, °C	ASTM D-97	-45
Colour	Visual	Red
Viscosity index	ASTM D-2270	163
Kinematic viscosity at 40°C (cSt)	ASTM D-445	27,38
Kinematic viscosity at 100°C (cSt)	ASTM D-445	5,82

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2023 Mitsuo Oil Corporation, Japan.