

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.ip

quality.always

MJ-443. MITASU GEAR OIL GL-4 75W-90 Synthetic Blended

MITASU GEAR OIL GL-4 75W-90 Synthetic Blended – multipurpose synthetic blended gear oil, formulated with synthetic base oils and a balanced additive package, safe for non-ferrous metals and alloys.

1L

APPLICATION


MITASU GEAR OIL GL-4 75W-90 Synthetic Blended is designed for use in mechanical (manual and robotic) gear boxes, transfer boxes and steering mechanisms as well as main gears of cars, buses, SUVs, trucks and other vehicles where the manufacturer recommended oil with a viscosity of SAE 75W-90 and API GL-4 standard *.

SPECIFICATIONS / APPROVALS

4L

API GL-4

APPLICATION BENEFITS




bronze, copper and etc · Stable performance at temperatures as low as -40 ° C

MITASU GEAR OIL GL-4 75W-90 Synthetic Blended provides:

- · Increased transmission life
- · Increased oil change interval
- · Protection from corrosion







20L

200L

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	75W-90
Density at 15°C	ASTM D-4052	0,8769
Flash point, °C	ASTM D-92	200
Pour point, °C	ASTM D-97	-40
Colour	ASTM D-1500	<0,5
Viscosity index	ASTM D-2270	192
Kinematic viscosity at 40°C (cSt)	ASTM D-445	92,05
Kinematic viscosity at 100°C (cSt)	ASTM D-445	16,15

Due to continual product research and development, the information contained herein is subject to change without notification.