



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-511. MITASU ULTRA PSF-II 100% Synthetic

MITASU ULTRA PSF-II 100% Synthetic is a high performance fully synthetic power steering fluid manufactured from Group-IV PAO base stock combined with a unique group of enhancing additives that meets the HONDA and ACURA OEM (Original Equipment Manufacturer) requirements.

APPLICATION

MITASU ULTRA PSF-II 100% Synthetic is recommended for use as a power steering fluid for HONDA, ACURA, ROVER and other vehicles. It provides for a stable operation in a wide range of temperatures and extended service life.



1L



4L



20L



200L

THIS PRODUCT MEETS THE REQUIREMENTS OF

- HONDA ULTRA PSF-II
- HONDA PSF Type S
- HONDA PSF Type V
- HONDA 08206-9002
- ACURA 08206-9002A



APPLICATION BENEFITS

MITASU ULTRA PSF-II 100% Synthetic offers:

- Compliance with the requirements of manufacturers of OEM (Original Equipment Manufacturer)
- Stable performance characteristics in a wide range of temperatures
- Proper functioning of power steering in various types of operating modes
- Excellent protection against wear

The latest technologies of MITASU OIL CORPORATION, Japan enable products manufactured by the company to exceed the requirements of most Japanese, American and European car manufacturers. Mitsasu Oil Corporation catalogue will help you to determine the correct product for your vehicle.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8347
Flash point, °C	ASTM D-92	200
Pour point, °C	ASTM D-97	-45
Colour	Visual	Slightly Haze
Viscosity index	ASTM D-2270	232
Kinematic viscosity at 40°C (cSt)	ASTM D-445	56,23
Kinematic viscosity at 100°C (cSt)	ASTM D-445	12,68

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2011 Mitsasu Oil Corporation, Japan.