

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

quality.always

MJ-546. MITASU HYDRAULIC OIL AW-100

MITASU HYDRAULIC OIL AW-100 – anti-wear hydraulic oil formulated from a high quality hydrocracked base oil and modern additive package with low Zinc content. It has anti-foaming ability, provides protection from wear and rust and has excellent filterability.

MITASU Japan Japan Japan Japan

20L

APPLICATION

MITASU HYDRAULIC OIL AW-100 is suitable for machinery, pumps and transmissions of heavy vehicles, construction, road and pit-run equipment, as well as for industrial and special equipment requiring hydraulic oil of certain viscosity index and characteristics, to ensure performance in moderate and low temperatures.



200L

THIS PRODUCT MEETS THE REQUIREMENTS OF

- · DENISON HF-0, 1, 2
- · DENISON T6H20C Hybrid Pump
- · VICKERS M-2950-S
- · VICKERS Vane Pump test (DIN 51589) PART 2 at 4.4 mg level
- · VICKERS 35VQ25A
- · CINCINNATI MACHINE P-68, P-69, P-70
- · US STEEL 127, 136
- · DIN 51524 PART 1 (HL), 2 (HLP)
- · DIN 51589 PART 1 at 6 min. level
- · AFNOR NF E 48-603 (HL)
- · FZG A/8.3/90 Load test (DIN 51354) at 12th Stage level

APPLICATION BENEFITS

MITASU HYDRAULIC OIL AW-100:

- · Protects hydraulic systems from wear
- · Has anti-foaming properties
- · Prevents corrosion
- · Has excellent filterability
- · Fully compatible with seal materials

The latest technologies of MITASU OIL CORPORATION, Japan enable hydraulic oils manufactured by the company to meet the requirements of a large number of hydraulic equipment manufacturers.



Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8780
Flash point, °C	ASTM D-92	228
Pour point, °C	ASTM D-97	-21
Colour	ASTM D-1500	<0,5
Viscosity index	ASTM D-2270	98
Kinematic viscosity at 40°C (cSt)	ASTM D-445	97,50
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,30

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2012 Mitasu Oil Corporation, Japan.

