



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-922. MITASU Racing 2T Motorcycle Synthetic Oil



1L



4L

MITASU Racing 2T Motorcycle Synthetic Oil is a high quality two-stroke engine oil with synthetic technology and an ash-free additive package. The product guarantees optimum wear protection and prevents deposits from developing in the engine. The product is blue in colour and has a distinctive strawberry scent.

APPLICATION

MITASU Racing 2T Motorcycle Synthetic Oil is designed to be either mixed with fuel* or used in separate lubrication of heavy and medium duty two-stroke engines of sports motorcycles, scooters, ATVs, small gasoline generators, lawn mowers and other equipment.

* For a mixing ratio of MITASU Racing 2T Motorcycle Synthetic with fuel, please follow the equipment manufacturer's recommendations.

SPECIFICATIONS / APPROVALS

- API TC
- JASO FC

APPLICATION BENEFITS

MITASU Racing 2T Motorcycle Synthetic provides:

- Easy mixing with fuel
- Superior wear protection
- Protection from deposits in the engine and the exhaust system
- Stable performance of the ignition system
- Low smoke

The latest technologies of MITASU OIL CORPORATION, Japan enable the two-stroke engine oils manufactured by the company to exceed the requirements of the following car manufacturers: YAMAHA, HONDA, SUZUKI, KAWASAKI, KTM, HUSQVARNA, APRILIA, BENELLI and others.

TECHNICAL CHARACTERISTICS

Technical Properties	Method	Result
Density at 15°C	ASTM D-4052	0,8750
Flash point, °C	ASTM D-92	95
TBN (mg KOH/g)	ASTM D 2896	1,4
Pour point, °C	ASTM D-97	-15
Colour	Visual	Blue
Viscosity index	ASTM D-2270	126
Kinematic viscosity at 40°C (cSt)	ASTM D-445	53,90
Kinematic viscosity at 100°C (cSt)	ASTM D-445	8,30

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2013 Mitasu Oil Corporation, Japan.

