



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitsuoil.co.jp

MJ-943. MITASU 4-STROKE MA2 10W-30



0,8L, 1L

MITASU 4-STROKE MA2 10W-30 is a premium quality four-stroke engine oil formulated with a high quality base and a modern additive package. Highly resistant to oxidation, the product guarantees optimum wear protection and prevents deposits in the engine.

APPLICATION

MITASU 4-STROKE MA2 10W-30 is designed for use in the lubricating systems of air-cooled and water-cooled 4T scooter and motorcycle engines, including those, operation continuously under high load conditions. It meets the requirements of JASO MA2 ensures precision operation of the wet-clutch in 4T motorcycles with an integrated transmission, is compatible with aftertreatment systems.

SPECIFICATIONS / APPROVALS

- API SL/SJ
- JASO MA2

APPLICATION BENEFITS

MITASU 4-STROKE MA2 10W-30 provides:

- Superior wear protection
- Protection from deposits in the engine
- Fuel economy

The latest technologies of MITASU OIL CORPORATION, Japan enable the four-stroke motorcycle engine oils, manufactured by the company, to exceed the requirements of such motorcycle manufacturers as HONDA, SUZUKI, YAMAHA and others.

TECHNICAL CHARACTERISTICS

Technical Property	Method	Result
SAE viscosity classification	SAE J300	10W-30
Density at 15°C	ASTM D-4052	0,8620
Flash point, °C	ASTM D-92	218
TBN (mg KOH/g)	ASTM D-2896	5,53
Pour point, °C	ASTM D-97	-30
Colour	ASTM D-1500	<2,0
Viscosity index	ASTM D-2270	155
Kinematic viscosity at 40°C (cSt)	ASTM D-445	69,80
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,30

Due to continual product research and development, the information contained herein is subject to change without notification

© 2020 Mitsuru Oil Corporation, Japan.

