



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-954. MITASU SUPERIOR 4-STROKE SN/MA2 15W-50 Synthetic Tech



0,8L, 1L

MITASU SUPERIOR 4-STROKE SN/MA2 15W-50 Synthetic Tech is a specialised four-stroke motorcycle engine oil formulated with synthetic technology combining premium quality base stock and a patented high-tech ZDDP (ZincDialkylDithioPhosphate) additive package that provides superior wear protection. The product meets the latest API SN and JASO MA2 specifications.

Compared to previous generation oils, MITASU SUPERIOR 4-STROKE SN/MA2 15W-50 Synthetic Tech offers higher oxidation resistance, prevents deposit formation throughout the engine, and extends the service life of catalytic converters in the engine exhaust system while meeting modern environmental standards.

APPLICATION

MITASU SUPERIOR 4-STROKE SN/MA2 15W-50 Synthetic Tech is designed for lubrication systems of modern and classic four-stroke air- and water-cooled motorcycle engines. It guarantees reliable wear protection in hot climates as well as under prolonged high load operating conditions. By meeting JASO MA2 requirements the product ensures high-precision wet clutch operation in motorcycle engines with integrated transmissions.

SPECIFICATIONS/APPROVALS

- API SN
- JASO MA2

APPLICATION BENEFITS

MITASU SUPERIOR 4-STROKE SN/MA2 15W-50 Synthetic Tech ensures:

- Superior wear protection
- Exceptional cleanliness of the combustion chamber and the cylinder/piston group
- Excellent performance at high ambient temperatures

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company for four-stroke motorcycle engines to exceed the requirements of such motorcycle manufacturers as ATK, BMW, DUCATI, HARLEY-DAVIDSON, HYOSUNG, TRIUMPH, SUZUKI, ROYAL ENFIELD and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	15W-50
Density at 15°C	ASTM D-4052	0,8750
Flash point, °C	ASTM D-92	220
TBN (mg KOH/g)	ASTM D-2896	7,20
Pour point, °C	ASTM D-97	-27
Colour	ASTM D-1500	2,5
Viscosity index	ASTM D-2270	153
Kinematic viscosity at 40°C (cSt)	ASTM D-445	157,70
Kinematic viscosity at 100°C (cSt)	ASTM D-445	20,62

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2020 Mitsuru Oil Corporation, Japan.

