



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
 Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
 E-mail: info@mitasuoil.co.jp

MJ-F11. MITASU SPECIAL F 5W-30 100% Synthetic

MITASU SPECIAL F 5W-30 100% Synthetic is a full SAPS product, intensified with a powerful package of high-tech anti-wear and detergent-dispersant additives, to meet the latest specification of FORD WSS-M2C913-D to oils with extended (Long Life) service interval.

APPLICATION

MITASU SPECIAL F 5W-30 100% Synthetic is ideally suited for modern diesel and petrol engines, as well as dual fuel engines running on diesel, biofuel B7, and liquefied petroleum gas (LPG), equipped with Catalytic Converters (CAT) and Diesel Particulate Filters (DPF), requiring ACEA A5/B5 and A1/B1 oils.

This product meets the requirements for anti-wear protection of the primary timing chain and improved compatibility with the gasket and drive belt materials.

SPECIFICATIONS / APPROVALS

- FORD WSS-M2C913-D approved
- API SL/CF
- ACEA A5/B5-10
- ACEA A1/B1-10
- RENAULT RN0700
- Exceeds the requirements of FORD WSS-M2C913-A/B/C



APPLICATION BENEFITS

MITASU SPECIAL F 5W-30 100% Synthetic offers the following benefits:

- Best wear protection by full SAPS technology
- The level of quality, specified by OEM
- Improved fuel economy
- Excellent antioxidant properties
- Easy start-up at low temperatures
- All-year-round application

Significantly exceeds international specifications such as API SL/CF, ILSAC GF-3 and suitable for most cars, manufactured by: JAGUAR, FIAT, OPEL, LAND ROVER, TOYOTA, HONDA, SUZUKI, SUBARU, MITSUBISHI, HYUNDAI, KIA and many others

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	5W-30
Density at 15°C	ASTM D-4052	0,8569
Flash point, °C	ASTM D-92	216
TBN (mg KOH/g)	ASTM D-2896	10,10
Pour point, °C	ASTM D-97	-39
Colour	ASTM D-1500	<3,0
Viscosity index	ASTM D-2270	164
Kinematic viscosity at 40°C (cSt)	ASTM D-445	66,94
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,33

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2014 Mitsuru Oil Corporation, Japan.



1L



4L



20L



200L