



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-326. MITASU CVT FLUID NS-2 100% Synthetic



1L



4L



20L



200L

MITASU CVT FLUID NS-2 100% Synthetic is a fully synthetic all-purpose transmission fluid for use with automobiles with continuously variable transmission (variator), where the fluid of NS-2 type is recommended. It is completely suitable for NISSAN automobiles, as well as for the other Japanese and Korean automobiles, and automobiles from other countries. It has excellent anti-vibration properties. The product color is green.

Excellent technical specifications of this product ensure the proper operation of a variable speed type transmission in various types of operating modes. Product's high viscosity index helps to minimize the negative effects of the intensive operating conditions. MITASU CVT FLUID NS-2 100% Synthetic designed for a variable speed type transmissions, meets the requirements of JASO 1A (Japanese Automotive Standards Organization) and exceeds the requirements of NISSAN car manufacturer.

APPLICATION

MITASU CVT FLUID NS-2 100% Synthetic is used for a wide range of automobiles with the variable transmissions.

THIS PRODUCT MEETS THE REQUIREMENTS OF

- NISSAN CVT FLUID NS-2



APPLICATION BENEFITS

MITASU CVT FLUID NS-2 100% Synthetic provides:

- Stable performance in the widest possible range of temperatures
- Extended drain interval
- Maximum friction reduction

The latest technologies of MITASU OIL CORPORATION, Japan enable fluids for automobiles with continuously variable transmission (CVT) manufactured by the company to exceed the requirements of such car manufacturers as NISSAN, MAZDA, SUZUKI and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
Density at 15°C	ASTM D-4052	0,8476
Flash point, °C	ASTM D-92	202
Pour point, °C	ASTM D-97	-45
Colour	Visual	Green
Viscosity index	ASTM D-2270	169
Kinematic viscosity at 40°C (cSt)	ASTM D-445	30,62
Kinematic viscosity at 100°C (cSt)	ASTM D-445	6,40

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2017 Mitasu Oil Corporation, Japan.