



MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

quality.always

MJ-411. MITASU GEAR OIL GL-5 75W-90 LSD 100% Synthetic

MITASU GEAR OIL GL-5 75W-90 LSD 100% Synthetic is a multi-purpose transmission oil, scientifically developed to meet the most stringent requirements of world car manufacturers for modern vehicles, equipped with any bevel or hypoid gearboxes.

APPLICATION

MITASU GEAR OIL GL-5 75W-90 LSD 100% Synthetic – is a multi-purpose transmission oil developed especially for use in intensive operating conditions. It ensures a high degree of protection against wear and ensures low noise levels. It is suitable for a wide application in transmissions, differentials and axles, including those equipped with LSD (Limited Slip Differential) and steering equipment of passenger cars, trucks, construction and agricultural equipment, where API GL-5 oil is recommended (operating under heavy loads conditions).

SPECIFICATIONS / APPROVALS

- API GL-5
- API MT-1
- PG-2
- Limited Slip
- MACK GO-J
- MIL-PRF-2105E



APPLICATION BENEFITS

MITASU GEAR OIL GL-5 75W-90 LSD 100% Synthetic provides:

- Efficient operation in the limited slip differentials (LSD)
- Stable performance in the widest possible range of temperatures
- Significant extension of drain interval
- Extended transmission service life
- Long-term friction protection
- Protection against rust

The latest technologies of MITASU OIL CORPORATION, Japan enable transmissions oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	75W-90
Density at 15°C	ASTM D-4052	0,8641
Flash point, °C	ASTM D-92	211
Pour point, °C	ASTM D-97	-42
Colour	ASTM D-1500	1,0
Viscosity index	ASTM D-2270	210
Kinematic viscosity at 40°C (cSt)	ASTM D-445	70,30
Kinematic viscosity at 100°C (cSt)	ASTM D-445	14,04

Due to continual product research and development, the information contained herein is subject to change without notification.

1L

4L

20L

200L

