



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-415. MITASU LX GEAR OIL GL-5 75W-85 LSD 100% Synthetic



1L



4L



20L



200L

MITASU LX GEAR OIL GL-5 75W-85 LSD 100% Synthetic is a fully synthetic low-viscosity transmission oil enhanced by a new generation of highly technological additives to meet the TOYOTA OEM (Original Equipment Manufacturer) requirements. Improves fuel efficiency. Meets the requirements of the latest transmissions, including those with a limited slip differential.

APPLICATION

MITASU LX GEAR OIL GL-5 75W-85 LSD 100% Synthetic is intended for modern car transmissions where the manufacturer recommends a low-viscosity API GL-5 oil. It ensures a high degree of protection against wear and low noise levels. Suitable for a wide application in transmissions, differentials and axles, including those with a LSD (Limited Slip Differential), and steering systems of passenger cars, trucks, construction and agricultural equipment.

SPECIFICATIONS / APPROVALS

- API GL-5
- LS type (Limited Slip)
- TOYOTA / LEXUS 08885-02606
- TOYOTA / LEXUS 08885-81070
- TOYOTA / LEXUS 08885-02506
- TOYOTA / LEXUS 08885-81060
- MERCEDES-BENZ 235.7 / 235.74
- MERCEDES-BENZ 239.71



APPLICATION BENEFITS

MITASU LX GEAR OIL GL-5 75W-85 LSD 100% Synthetic provides:

- High degree of protection against wear and low noise levels
- Efficient operation in limited slip differentials (LSD)
- Stable performance at temperatures as low as - 42 ° C
- High fuel efficiency
- Significant extended drain interval
- Long-term friction protection

By utilizing the latest technologies available, MITASU OIL CORPORATION, Japan has been able to develop transmission oils that exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	75W-85
Density at 15°C	ASTM D-4052	0,8643
Flash point, °C	ASTM D-92	210
Pour point, °C	ASTM D-97	-42
Colour	ASTM D-1500	<1,5
Viscosity index	ASTM D-2270	202
Kinematic viscosity at 40°C (cSt)	ASTM D-445	62,80
Kinematic viscosity at 100°C (cSt)	ASTM D-445	12,50
Brookfield Viscosity at -40°C (mPa.s)	ASTM D-2983	81250

Due to continual product research and development, the information contained herein is subject to change without notification.