



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

MJ-P03. MITASU GOLD PAO Plus SP/CF 0W-30 100% Synthetic



1L



4L



20L



200L

MITASU GOLD PAO Plus SP/CF 0W-30 100% Synthetic is the top range Mid SAPS motor oil, formulated with a Group IV PAO (Poly-Alpha-Olefin), Group III fully synthetic base oils and reinforced with a powerful additive package. The product meets the latest OEM requirements to oils with extended (Long Life) service interval, the latest API SP category of the American Petroleum Institute and the highest ILSAC GF-6A quality standard established by the International Lubricants Standardization and Approval Committee. It has a low tendency to form deposits on engine parts. It provides easy start-up at temperatures as low as - 42 °C

APPLICATION

MITASU GOLD PAO Plus SP/CF 0W-30 100% Synthetic is ideal for modern cars powered by gasoline and diesel engines with or without turbocharging, direct injection and multi-stage emission-reducing systems. The product's operational and environmental characteristics meet the newest MB-Approval 229.61 standard. Suitable for use in European, North American and East Asian vehicles requiring low ash motor oils - ACEA C2 or JASO DL-2 and DL-1. Recommended for year-round application.

SPECIFICATIONS / APPROVALS

- API SP/CF
- ACEA C2
- ILSAC GF-6A
- CHRYSLER MS-13340
- FIAT 9.55535-DS1/GS1
- MB-Approval 229.61
- BMW Longlife-12 FE
- FORD WSS-M2C 950-A
- PSA B71 2312
- STJLR.03.5007



APPLICATION BENEFITS

All-season fully synthetic motor oil MITASU GOLD PAO Plus SP/CF 0W-30 100% Synthetic provides:

- OEM (Original Equipment Manufacturer) level of quality
- Low Speed Pre-Ignition (LSPI) protection of new generation turbocharged gasoline direct-injection engines
- Longer life of after treatment systems as CAT and DPF
- Extended drain interval
- Stable performance in a wide range of temperatures due to PAO base oil

The latest technologies of MITASU OIL CORPORATION, Japan enable engine oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, SUZUKI, SUBARU, DAIHATSU, FORD, FIAT, HYUNDAI, JAGUAR, KIA, LAND ROVER, VOLVO and many others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	0W-30
Density at 15°C	ASTM D-4052	0,8470
Flash point, °C	ASTM D-92	216
TBN (mg KOH/g)	ASTM D-2896	9,40
Pour point, °C	ASTM D-97	-42
Colour	ASTM D-1500	<2,5
Viscosity index	ASTM D-2270	170
Kinematic viscosity at 40°C (cSt)	ASTM D-445	63,15
Kinematic viscosity at 100°C (cSt)	ASTM D-445	11,10

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2024 Mitsuru Oil Corporation, Japan.