

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku,Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

MATERIAL SAFETY DATA SHEET

1.	PRODUCT IDENTIFICATION AND COMPANY												
	Issue Date	01.0	01.01.2023										
	Validity Period	3 уе											
	Product Name	МІТ	MITASU ATF 9 HP 100% Synthetic MJ-309										
	Product Code	MJ-3											
		Mitasu Oil Corporation											
	Producer	Tel:	1-2-9, Nishi Shimbashi, Minato-Ku,Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp										
2.	COMPOSITION												
	Base Oil Content	82	-	92	%								
	Additives Content	8	-	18	%								
3.	HAZARDS IDENTIFI		N										
0.	Human Health Product is not hazardous.												
	Eye Contact		Slightly irritant.										
	Inhalation	Repeated and prolonged over-exposure to oil mists may cause irritation											
	Ingestion	Mini											
	Safety Hazards	Not	classi	fied a	s fla	mmable but wi	ill burn.						
	Environmental Hazards	Not	Not readily biodegradable.										
4.	FIRST AID												
Eye Contact Flush eyes with large amount of water until irritation subsides. If irritation get medical attention. Skin Contact Flush with large amount of water; use soap if available. Remove contar clothing. If irritation persists, get medical attention.								If irritation persists,					
								ve contaminated					
	Inhalation	Rem	nove to	o fres	h air	. If rapid recov	ery does	not occur, get med	ical attention.				
Ingestion Do not induce vomiting. If rapid recovery does not occur, get medical attention									nedical attention.				
	5												

	Flash Point	>	208	°C									
	Flammable Limit	Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds.											
	Autoignition Temp	>	303	°C									
	Specific Hazards	Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds.											
	Fire Fighting	Use dry chemical, foam or carbon dioxide to extinguish fire. Water may cause splattering or frothing. Use water to cool and protect fire-exposed material. Wear protective equipment during fire fighting.											
6.	ACCIDENTAL RELEAS	E MEASURES											
	Clean-up Procedure	Stop the source of leak or release and contain spill if possible. Cover spill with generous amount of inert absorbent material such as sand or earth. Sweep up and remove to suitable, clearly marked containers for disposal in accordance with local regulati.											
7.	HANDLING AND STOP	RAGE	1										
	Handling	equi	Handling temperatures should not exceed 70°C. Wear proper safety protective equipment. Wash hands thoroughly after handling. Water contamination and spillage should be avoided.										
	Storage	toxic	Storage temperatures should be maintained between 0 to 50°C. Odorous and toxic fumes may be evolved from decomposition of product if stored above the safe temperature.										
		(9=1											
8.	EXPOSURE CONTROL		RSONA		KOI	ECTION							
	Exposure Limits		Threshold Limit Values for oil mist is recommended to be controlled at 5 mg/m3 or lower for exposure of 8 hours daily.										
	Ventilation	Exha	aust vei	ntilat	ion t	o keep below expo	sure	limits.					
	Eye Protection	Wea	ar safety	y gla	sses	or face shields if	splas	hing is likely to occur.					
	Skin Protection	Avoi	d repea	ated	and	prolonged contact	with	product. Use oil resistant glov	es.				
	Respiratory Protection	Not	normall	ly rec	quire	d unless in confine	ed spa	ace.					
	Body Protection		Use proper protective equipment to avoid contact. Wear PVC apron if splashes are likely to occur.										
9.	PHYSICAL AND CHEMICAL PROPERTIES												
	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.												
	TEST DESCRIPTION UNIT METHOD TYPICAL RESULTS												
	Color		-			Visual		Red					
	Density at 15 °C		kg/	/1		D 4052		0,8360					
	Kinematic Viscosity at 40 °C		cS	t		D 445		27,20					
	Kinematic Viscosity at 100 °C		cS	t		D 445		5,96					

	Viscosity Index	-		D 2270	174								
	Flash Point, COC	°C		D 92	208								
	Pour Point	°C		D 97	-42								
10.	STABILITY AND REAC	ידועוד ע											
10.	Stability Product is stable under normal use conditions.												
	Thermal Decomposition	Carbon monoxide, carbon dioxide, oxides of sulphur and nitrogen and organic and inorganic compound may evolve when subject to heat or combustion.											
	Hazardous Polymerisation	Will not occur under normal conditions.											
	Incompatible Materials	als Strong oxidizing agents. Strong acids											
1 1													
11.	TOXICOLOGICAL INFORMATION												
	Basis	No toxicological data is available for this product. Information is provided based on the additives, other components and base stock used.											
	Acute Exposure Oral	LD 50 expected	l to k	be above 2000 mg/kg									
	Acute Exposure Skin LD 50 expected to be above 2000 mg/kg												
Inhalation Repeated or prolonged exposure to oil mists may cause irritation.													
	Eye Irritation	re Irritation Slightly irritant.											
Skin Irritation Not a skin irritant unless repeated or prolonged contact.													
	Respiratory Irritation	Slight irritant.											
	Carcinogenicity	No data to sugg	jest	that product is carcin	ogenic.								
	Mutagenicity	No data to suggest that product is mutagenic.											
	Other Information	Brief contact with used oil is not expected to have serious effect in humans if the oil is removed thoroughly by washing with soap and water.											
		Used engine oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they present risks to health and the environment on disposal. All used oils should be handled with caution.											
12.													
	Basis			is available for this pr components and bas	oduct. Information is provided b e stock used.	ased on							
	Mobility			environmental condition and will not be mobile	ons. Floats on water. It e.								
	Persistence/ Degradability				ents are expected to be inherent components that may persist in								

	Bioaccumulation	Has the potential to bioaccumulate.												
	Ecotoxicity	Poor soluble mixture. Practically non-toxic to aquatic organisms. May cause physical fouling of aquatic organisms.												
13.	DISPOSAL CONSIDE	CONSIDERATION												
	Product Disposal		Used or waste oil should be recycled or disposed off in conformity to local disposal regulations. Contact local authorities for approved disposal contractor.											
	Container Disposal	er Disposal Empty drums should be completely drained and sent to a drum reconditioner or properly disposed of. Non-reusable small containers should be recycled or disposed of. Ensure conformity to local disposal regulations.												
14.	TRANSPORT INFOR	MATIC	ON											
	General Information Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes.													
15.	REGULATORY INFO	RMAT	ION											
	Not Applicable.													
16.	OTHER INFORMATION													
	The above information is based on data of which we are aware and is believed to be correct as of the dathereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may sug modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination the suitability of the material for his particular purpose. Therefore, no warranty either express or implied merchantability or fitness for particular purpose is made with respect to the product or the information contained herein.													